

HEALTH IS THE HEART OF OUR BUSINESS.


HOLTER-RR 24H ABPM

GENTLE AMBULATORY BLOOD PRESSURE MONITORING DIAGNOSTICS

Meaningful data: The Holter-RR guarantees reliable ambulatory blood pressure monitoring.

The Auto Feedback Logic (AFL) allows quiet and fast readings with low cuff pressure.

For precise interpretation threshold tables for children and adolescents are integrated.



MANAGE COMPLEX DATA EASILY

AMEDTEC ECG_{pro}

TECHNICAL DATA

Pressure measurement range	systolic 60 to 290 mmHg diastolic 30 to 195 mmHg
Accuracy	+/-3 mmHg in the range indicated
Static pressure range	0 to 300 mmHg
Pulse range	30 to 240 beats per minute
Method	oscillometric
Measurement intervals	0, 1, 2, 3, 4, 5, 6, 10, 12, 15, 20 or 30 measurements per hour
Monitoring protocols	2 programmable and 7 fixed protocols
Storage capacity	300 measurements
Operating temperatures	+10 °C bis +40 °C
Operating humidity	15 % to 90 %
Dimensions	128 mm x 75 mm x 30 mm
Weight	approx. 240 g incl. rechargeable batteries
Power supply	2 Mignon AA alkaline or rechargeable batteries
Interfaces	USB or serial (RS232) cable

ACCESSORIES




pouch for Holter-RR



cuffs in size XS, S, M, L, XL

ECONOMEDICAL
PO BOX 6119
GOSFORD WEST NSW 2250
Phone: 0405 605 930
peter@economedical.com.au
www.economedical.com.au



ABP monitor manufacturer:
IEM GmbH
Gewerbepark Brand 42
52078 Aachen, Germany

CE 0494 ABPM software
0044 ABPM recorder

Errors and omissions excepted
M0731 018-0402-2_04